




## CABLE-4-20MA

### 4 to 20 mA Input

Cable, 18.5 inches in length, for connecting a sensor with a 4-20mA output to a HOBO U12, UX120, MX1100, or ZW series external-channel data logger, to expand the range of measurement options and applications.



#### Key Advantages:

- 18.5 inches in length
- Can be plugged directly into the external input jacks of U12, UX120, or ZW series loggers to expand the range of measurement options and applications.

## HOBO CABLE-4-20MA Specifications

**Measurement range:** 0 to 20.1 mA

**Accuracy with U12:**  $\pm 0.02$  mA  $\pm 2.5\%$  of absolute current

**Accuracy with ZW:**  $\pm 0.015$  mA  $\pm 2.0\%$  of absolute current

**Accuracy with UX120-006M, MX1104, and MX1105:**  $\pm 0.001$  mA  $\pm 0.2\%$  of absolute current

**Resolution with U12 and ZW:** 0.03% of full scale

**Resolution with UX120-006M, MX1104, and MX1105:** 0.002% of full scale

**Cable length:** 47 cm (18.5 inches)

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532