



## HOBO<sup>®</sup> M-RSA

### Solar Radiation Shield (assembled)

Preassembled for quick deployment, the solar radiation shield is recommended for temperature and relative humidity measurement accuracy in locations exposed to direct or reflected solar radiation. Mounts on tripods, masts, or flat vertical surfaces. The following loggers require mounting brackets for use with the M-RSA:

HOBO MX2301 or MX2305 loggers require the MX2300-RS-BRACKET HOBO U22 or U23-001 loggers require the U23 Clamp Kit .



## HOBO M-RSA Specifications

**Height:** 152 mm (6.0 inches); 165 mm (6.5 inches) with bracket

**Width:** 210 mm (8.3 inches)

**Depth:** 187 mm (7.4 inches); bracket protrudes an additional 44 mm (1.8 inches) from shield

**Mounting:** includes 1-5/8" u-bolts for mast mounting, or mount on a flat surface with user-supplied screws

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532