



HOBO[®] T-EG-x000-2775 Sensor

Rogowski Coil Sensor

Rope CTs are excellent for bus-bars and large switch-gear applications. Self-powered rope CTs are flexible and easy to install, but will not be accurate below 30A. Each CT includes the two-pin CT connector plug.

Technical Specifications

333 mVrms at rated output Accurate within 1% from 30A to stated current rating 6' twisted pair lead with CT connector
Wide current input range from 5A – 50,000A AC Note: 30A minimum current required at all times. No external integrator required

Key Advantages:

- Designed to be used where regular split core CTs cannot fit
- Simple installation



HOBO T-EG-x000-2775 Sensor Specifications

Model	Window Size	Coil Length	External Diameter	Coil Diameter
T-EG-4000-2775	4.17"	15.75"	5.63"	15.5"
T-EG-7000-2775	7.01"	23.62"	8.13"	15.5"

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532