

## InTemp<sup>®</sup> CX402-Txxx Data Logger

### Bluetooth Temperature with Glycol Bottle (Logistics)

InTemp<sup>®</sup> CX402-Txxx (with Glycol Bottle) data loggers monitor temperatures in refrigerators, freezers and other temperature-controlled environments to comply with global GDP requirements. The loggers communicate wirelessly via Bluetooth Low Energy to mobile devices. Using the InTemp app, you can easily view data, check logger status, set alarms, and create and share secure PDF reports for streamlined reporting and regulatory compliance. All loggers feature a built-in LCD display to view current and daily min and max temperatures, advanced audible and visual alarm capabilities for notification of temperature excursions, an internal sensor for ambient temperature monitoring, and a single-point NIST Certification of Calibration for both the logger body and probe.

With the optional CX Gateway, you can get remote notifications of temperature excursions and automatically download data from loggers within range of the device. Learn more about the CX Gateway here.

Models are available with a 2- or 4-meter external temperature probe attached to a Glycol bottle used to insulate the probe and delay thermal response times.


#### Key Advantages:

- Integrates with mobile and cloud platforms for a 21 CFR Part 11 compliant solution
- Easy-to-read display with current and daily min/max temperatures
- Bluetooth transmission of data and alarm states
- Logger setup and download of data in seconds – without a PC or cable
- Real-time alerts and automatic data downloads with optional CX Gateway device
- +/- 0.5C accuracy for reliable temperature readings
- Battery-powered to guard against local power loss
- Several Glycol bottle/probe-only options available
- **Includes 1-year NIST calibration, per USP guidelines**



## InTemp CX402-Txxx Data Logger Specifications

### Logger

<b>Radio Power</b>	1 mW (0 dBm)
<b>Transmission Range</b>	Approximately 30.5 m (100 ft) line-of-sight
<b>Wireless Data Standard</b>	Bluetooth Low Energy (Bluetooth Smart)
<b>Logger Operating Range</b>	-30° to 70°C (-22° to 158°F), 0 to 95% RH (non-condensing)
<b>Logging Rate</b>	1 second to 18 hours
<b>Battery Type</b>	Two AAA 1.5 V alkaline or lithium batteries, user replaceable
<b>Battery Life</b>	1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive report generation, numerous audible alarms, and paging all impact battery life.
<b>Memory</b>	128 KB (84,650 measurements, maximum)
<b>Full Memory Download Time</b>	Approximately 60 seconds; may take longer the farther the device is from the logger
<b>LCD</b>	LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
<b>Dimensions</b>	9.4 x 4.5 x 2.59 cm (3.7 x 1.77 x 1.02 inches)
<b>Weight</b>	90.2 g (3.18 oz)
<b>Environmental Rating</b>	IP54
<b>CE</b>	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).
<b>Compliance Marks</b>	

### External Temperature Probe

<b>Range</b>	-40° to 100°C (-40° to 212°F)
<b>Accuracy</b>	±0.5°C from -15° to 80°C (±0.9°F from 5° to 176°F) ±1.0°C from -40° to -15°C (±1.8°F from -40° to 5°F) ±0.7°C from 80° to 100°C (±1.3°F from 176° to 212°F)
<b>Resolution</b>	0.024°C at 25°C (0.04°F at 77°F)
<b>Cable Length</b>	2 or 4 meter (6.56 or 13.12 feet) flat ribbon cable
<b>NIST Calibration</b>	Single-point NIST calibration, probe and logger body
<b>Probe Dimensions</b>	Food-grade stainless steel probe with pointed tip, 53.34 mm (2.1 inches) long, 3.18 mm (0.125 inches) diameter

### Ambient Temperature Sensor

<b>Range</b>	-30° to 70°C (-22° to 158°F)
<b>Accuracy</b>	±0.5°C from -15° to 70°C (±0.9°F from 5° to 158°F) ±1.0°C from -30° to -15°C (±1.8°F from -22° to 5°F)
<b>Resolution</b>	0.024°C at 25°C (0.04°F at 77°F)

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532