

M-RSA

Solar Radiation Shield (assembled)

For temperature and relative humidity measurement accuracy in locations exposed to direct or reflected sunlight; preassembled for quick deployment.

Important Information

HOBO MX2301 or MX2305 loggers require the MX2300-RS-BRACKET.
HOBO U22 or U23-001 loggers require the U23 Clamp Kit.



Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Solar Radiation Shield (assembled) (M-RSA) Specifications

Height: 152 mm (6.0 inches); 165 mm (6.5 inches) with bracket

Width: 210 mm (8.3 inches)

Depth: 187 mm (7.4 inches); bracket protrudes an additional 44 mm (1.8 inches) from shield

Mounting: includes 1-5/8" u-bolts for mast mounting, or mount on a flat surface with user-supplied screws