

S-BPB-CM50

Smart Barometric Pressure Sensor

A weatherproof smart sensor with a measurement range of 660 mb to 1070 mb; compatible with the HOBO Remote Monitoring System and HOBO Micro Station.



Supported Measurements

Barometric Pressure

Features

- Weatherproof housing enables mounting outside the station enclosure, so the station can maintain its weatherproof seal without having to be vented to the atmosphere
- Measures barometric pressure over a wide range
- Includes zip ties for mounting on mast; can also be mounted on flat surface with screws

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Smart Barometric Pressure Sensor (S-BPB-CM50) Specifications

Measurement range: 660 to 1070 mbar (19.47 to 31.55 in. Hg)

Accuracy: ± 3.0 mbar (0.088 in. Hg) over full pressure range at 25°C (77°F); maximum error of ± 5.0 mbar (0.148 in. Hg) over -40° to 70°C (-40° to 158°F)

Resolution: 0.1 mbar (.003 in. Hg)

Drift: 1.0 mbar (0.03 in. Hg) per year

Operating temperature range: -40° to 70°C (-40° to 158°F)

Environmental rating: Weatherproof

Dimensions: 6.4 cm (2.5 in) diameter x 5.1 cm (2 in) height

Weight: 96 gm (3.4 oz)

Bits per sample: 12

Number of data channels: 1 *

Measurement averaging option: Yes

Cable length available: 50 cm (20 in)

Length of Smart Sensor network cable: 50 cm (20 in)

Specification: This product meets CE specification EN61326-1 criterion C for ESD, criterion C for Radiated Immunity, criterion C for Fast Transient, criterion B for Conducted Immunity, criterion A for Power Frequency Magnetic Fields, and Class B for Radiated Emissions Group 1. To minimize measurement errors due to ambient RF, use the shortest possible probe cable length and keep the probe cable as far as possible from other cables.

* A single HOBO Weather Station can accommodate 15 data channels and up to 100 m (328 ft) of smart sensor cable (the digital communications portion of the sensor cables).