

TEL-7001

Telaire 7001 CO2 Sensor

Discontinued

The Telaire 7001 handheld carbon dioxide sensor features patented Absorption Infrared technology. Each sensor measures CO₂ and temperature and can calculate and display real-time ventilation rates. When combined with the HOBO U12 or ZW Series it can record CO₂, and when connected to an analog input on the H22, RX3000, or U30 Series it can record temperature and CO₂. The Telaire comes with an adapter but also operates up to 70 hours on 4 AA batteries (not included). The Telaire 7001 Co₂ Monitor measures and displays CO₂ and temperature data simultaneously, or CO₂ only with U12 logger.

[View upgrade options](#)



Supported Measurements

Carbon Dioxide, Temperature

Features

- Record 0 to 2500 ppm when using the CABLE-CO2 and a HOBO U12, UX120-006M, MX1100, or ZW series logger
- Record 0 to 4000 ppm when using the CABLE-2070 and a HOBO RX3000, H22, or U30 data logger
- AC power adapter included

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Telaire 7001 CO2 Sensor (TEL-7001) Specifications

Measurement Range

When using the [CABLE-CO2](#) and a [U12](#) or [ZW](#): 0 to 2500 ppm

When using the [CABLE-2070](#) and a [H22](#) or [U30](#): 0 to 4000 ppm

Telaire 7001 operating range: 32°F to 122°F (0°C to 50°C), 0 to 95% RH, non-condensing

Display resolution: ±1 ppm

Accuracy: ±50 ppm or 5% of reading, whichever is greater

Repeatability: ±20 ppm

Temperature dependence: ±0.1% of reading per °C or ±2 ppm per °C, whichever is greater, referenced at 25°C.

Pressure dependence: 0.13% of reading per mmHg (corrected via user input for elevation)

Response time: <60 seconds for 90% of step change

Warm-up time: <60 seconds at 72°F (22°C)

Calibration interval: 12 months Full factory calibration available by contacting GE Measurement & Control Solutions.

Battery type: Four AA batteries (not included)

Battery operation: 80 hours (alkaline)

External power supply specifications

AC/DC adapter (included)

Output: 6 VDC, 500mA output.

Power connector: Round barrel with 2.5mm ID , 5.5mm OD, 12mm long, center positive (+6 VDC), outer shell ground.