

UX120-017

HOBO 4-Channel Pulse Data Logger

Discontinued

A highly versatile, 4-channel energy data logger that combines the functionality of four separate loggers into one compact unit; standard memory model.

Important Information

Requires HOBOWare software and a USB cable. (Note: A USB cable is included w/HOBOWare Pro CD or USB software purchase). See compatible items below.



Compatible with
HOBOWare® Software

[View upgrade options](#)



Supported Measurements

AC Voltage, Amp Hour (Ah), Amps (A), Event, Kilowatt Hours (kWh), Kilowatts (kW), Motor On/Off, Power Factor (PF), Pulse Input, Runtime, State Open/Closed, Volt-Amp Reactive, Volt-Amp Reactive hour, Volt-Amps (VA), Volts (V), Water Flow, Watt Hours (Wh), Watts (W)

Features

- Simultaneously measures and records pulse signals, events, state changes, and runtimes
- Stores up to over 4 million measurements, enabling longer deployments with fewer site visits
- Maximum pulse rate – 120 Hz
- Pulse input range – 0 to 24VDC
- Streamlines deployment via a range of start/stop options, logger status LEDs, and high-speed USB 2.0 data offload
- Works with Onset's Energy & Power Meter to measure Power Factor (PF), Reactive Power (VAR), Watt Hours (Wh) and more. Learn how. The T-VER-E50B2 Energy and Power Meter outputs (3) sets of pulses which are logged by the UX120-017. These pulses represent Watt-hours, Amp-hours, and VAR-hours. HOBOWare software uses these pulse values to calculate AC Current, AC Voltage, kW, Power Factor, VARs, and VA. The formulas used in these calculations can be found here: 14993-A-Derived-Channels.zip
- Compatible with HOBOWare and HOBOWare Pro software for logger setup and graphing & analysis

What's in the box

- HOBO UX120-017 4-Channel Pulse Input Data Logger
- 4 mounting screws
- 2 magnets
- Hook & loop tape
- 4 terminal block connectors

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

HOBO 4-Channel Pulse Data Logger (UX120-017) Specifications

Inputs

External Contact Input:	Electronic solid state switch closure or logic driven digital signals to 24 V
Maximum Pulse Frequency:	120 Hz
Maximum State, Event, Runtime Frequency:	1 Hz
Bits:	4–32 bits depending on pulse rate and logging interval
Maximum Pulses Per Interval:	7,863,960 (using maximum logging rate)
Driven Logic Signal:	Input Low: ? 0.4 V; Input High: 3 to 24 V
Absolute Maximum Rating:	Maximum Voltage: 25 V DC Minimum Voltage: -0.3 V DC
Solid State Switch Closure:	Input Low: < 10 K?; Input High: > 500 K?
Internal Weak Pull-Up:	100 K?
Input Impedance:	Solid state switch closure: 100 K? pull up; Driven signal: 4.5 K?
Minimum Pulse Width:	Contact closure duration: 500 uS; Driven logic signal: 100 uS
Lockout Time:	0 to 1 second in 100 ms steps
Edge Detection:	Falling edge, Schmitt Trigger buffer
Preferred Switch State:	Normally open or Logic "1" state

Logging

Resolution:	Pulse: 1 pulse, Runtime: 1 second, State and Event: 1 State or Event
Logging Rate:	1 second to 18 hours, 12 minutes, 15 seconds
Time Accuracy:	± 1 minute per month at 25°C (77°F) (see Plot A on next page)
Battery Type:	Two AA alkaline or lithium batteries
Battery Life:	1 year, typical with logging intervals greater than 1 minute and normally open contacts

Memory

Memory:	UX120-017: 520,192 measurements (assumes 8-bit) UX120-017M: 4,124,672 measurements (assumes 8-bit)
Download Type:	USB 2.0 interface
Download Time:	30 seconds for UX120-017, 1.5 minutes for UX120-017M

Physical

Operating Range:	Logging: -40° to 70°C (-40° to 158°F); 0 to 95% RH (non-condensing) Launch/Readout: 0° to 50°C (32° to 122°F) per USB specification
Weight:	149 g (5.26 oz)
Size:	11.4 x 6.3 x 3.3 cm (4.5 x 2.5 x 1.3 inches)
Environmental Rating:	IP50



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).