

RS3-B

## Solar Radiation Shield

Use the RS3-B Solar Radiation Shield with HOBO external sensors for improved temperature measurement accuracy in locations exposed to sunlight



### Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532

## Solar Radiation Shield (RS3-B) Specifications

**Time response:** 2.5 times faster than the RS1 and M-RSA

**Wind resistance:** Tested in sustained winds up to 129 kph (80 mph), Tested in gusts up to 161 kph (100 mph)

### **Materials**

**Shield:** ASA styrene (UV-stable)

**Bracket:** Glass-filled nylon (UV-stable)

**Mounting hardware:** Stainless steel and brass

**Temperature:** -40° to 75°C (-40° to 167°F)

**Weight:** 113 g (4 oz)

**Height:** 89 mm (3.5 inches); 159 mm (6.25 inches) with bracket

**Diameter:** 102 mm (4 inches); bracket protrudes an additional 51 mm (2 inches) from shield

**Maximum Sensor Diameter:** 1.22 cm (0.48 inches)

**Mounting:** Up to 51 mm (2 inches) mast diameter with hose clamp; unlimited with screws

**Compatible sensors:** S-THC-M00x, S-TMB-M0xx, RXW-THC-xxx, RXW-TMB-xxx, TMCx-HD, and external sensors from U23-00x or MX230x.

**Note:** This shield does not protect sensors from light reflected from below the shield at some angles. For deployments over reflective surfaces, consider using Onset's [RS1](#) or [M-RSA](#) Solar Radiation Shields.