

U-DTW-1

HOBO Waterproof Shuttle

Provides convenient readout and relaunching of underwater and outdoor HOBO data loggers with an Optic USB interface, and is waterproof to 20m (66ft). Can also be used as a base station.

Important Information

HOBOWare Pro is required for this product.



Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

HOBO Waterproof Shuttle (U-DTW-1) Specifications

Compatibility:

All HOBO U-Series loggers with optic USB.

Not compatible with the HOBO U-Shuttle (U-DT-1)

Requirements: HOBOWare Pro 2.2 or greater

Compatible logger and matching coupler:

For UA Pendant (Part # COUPLER2-A)

For U20 Water Level (Part # COUPLER2-B)

For U22 Water Temp Pro v2 (Part # COUPLER2-C)

For UTBI TidbiT v2 (Part # COUPLER2-D)

For U23 HOBO Pro v2 (Part # COUPLER2-E)

Data capacity: 63 logger readouts of up to 64K each

Operating temperature: 0° to 50°C (32° to 122°F)

Storage temperature: -20° to 50°C (-4° to 122°F)

Wetted materials: Polycarbonate case, EPDM o-rings and retaining loop

Waterproof: to 20 m (66 feet)

Time accuracy: ± 1 minute per month at 25°C (77°F)

Logger-to-shuttle transfer speed: Reads out one full 64K logger in about 30 seconds

Shuttle-to-host transfer speed: Full shuttle offload (4 MB) to host computer in 10 to 20 minutes, depending on computer

Batteries: 2 AA alkaline batteries required for remote operation

Battery life: One year or at least 50 complete memory fills, typical use

Weight: 150 g (4 oz)

Dimensions: 15.2 x 4.8 cm (6.0 x 1.9 inches)

The CE Marking identifies this product as complying with the relevant directives in the European Union (EU).