

H08-006-04

## HOBO 4 External Channel Data Logger



Discontinued

This four-channel data logger accepts a wide range of external sensors in four separate external channels, and records up to 32,500 measurements. This four-channel data logger accepts a wide range of external sensors in four separate external channels, and records up to 32,500 measurements

### Important Information

This product is compatible with Boxcar, which is discontinued. However, users of our legacy products can still download the unsupported free version below:



Compatible with  
**BoxCar**

[View upgrade options](#)

### Supported Measurements

4-20mA, AC Current, AC Voltage, Carbon Dioxide, DC Voltage, Temperature

### Features

- 8-bit resolution
- Programmable start date/time
- Programmable sampling rate (0.5 second to 9 hours)

### Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

## HOBO 4 External Channel Data Logger (H08-006-04) Specifications

**Operating range (logger):** -4°F to +158°F (-20°C to +70°C), 0 - 95% RH non-condensing

**Time accuracy:** approx. ±1 minute per week (±100 ppm at +68°F or +20°C), full dependance shown in manual

**Measurement capacity:** 32,520 measurements total, stored in nonvolatile memory

Drop proof to 5'

**Size:** 2.4" H x 1.9" W x 0.8" D

**Weight:** approximately 1 oz.

**Battery:** CR-2032 (lithium), user-replaceable

**Battery life (continuous use):** 1 year

**Storage temperature:** -40°F to +167°F (-40°C to +75°C)