

T-MINOL-130

## Water Flow Meter Sensor

Discontinued

Measure cold and hot water flow rates with this compact water meter. The small-sized T-MINOL-130 is designed for deployment in apartments, assisted living communities, and other commercial buildings. Please note, the T-MINOL is configured for use with 3/4" pipes. (Use step-ups or step-downs to deploy the T-MINOL with 1/2" or 1" pipe diameters.) View MINOMESS 130 manual Enables monitoring hot or cold water usage.

[View upgrade options](#)



### Supported Measurements

Water Flow

### Features

- This adds the ability for users to monitor hot or cold water usage at an affordable price.

### Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532

## Water Flow Meter Sensor (T-MINOL-130) Specifications

**Measurement range:** .25 to 22.0

**Accuracy:** AWWA spec 97 - 103%

**Connection size:** ANSI/ASME B1.20.1-1983; 1-11.5 SNPSM thread; 5/8 x 3/4 in ID

**Dimensions:** length 5.12 in, width 2.5 in, height 3.15 in

**Cable length:** 59 in.

**Water temperature range:** 40F to 180F

**Meter max reading:** 99,999,999 US gal

**Resolution:** 1 contact closure per gal

**Body:** nickel-plated brass

**Weight:** 1.32 lbs

**Pressure drop:** < 8.70 psi typical @ 22 gpm; < 3.6 psi @ 11 gpm

**Reed switch:** dry contact