

S-RGC-M002

Davis® 0.01" Rain Gauge Smart Sensor

Discontinued

Compatible with HOBO weather stations, HOBOWare, and HOBOLink, this 0.01" rain gauge sensor features a plug-in modular connector for easy installation; requires no programming or extensive setup.



Compatible with
LI-COR Cloud® IoT Platform

[View upgrade options](#)

Supported Measurements

Rainfall

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Davis® 0.01" Rain Gauge Smart Sensor (S-RGC-M002) Specifications

Measurement Range	0 to 10.2 cm (0 to 4 in.) per hour, maximum 4,000 tips per logging interval
Accuracy	±4.0%, ±1 rainfall count between 0.2 and 50.0 mm (0.01 and 2.0 in.) per hour; ±5.0%, ±1 rainfall count between 50.0 and 100.0 mm (2.0 and 4.0 in.) per hour
Resolution	0.01 in. (S-RGC-M002) or 0.2 mm (S-RGD-M002)
Calibration	Requires annual calibration; can be field calibrated
Operating Temperature Range	0° to 50°C (32° to 122°F), survival -40° to 75°C (-40° to 167°F)
Environmental Rating	Weatherproof
Housing	UV-stabilized ABS plastic
Mechanism	Tipping bucket with magnetic reed switch pivots on metal shaft
Dimensions	16.5 cm opening diameter (6.5 in.) x 24 cm (9.5 in.) high; 214 cm ² (33.2 in. ²) collection area
Weight	1 kg (2 lb, 3 oz)
Bits per Sample	12
Number of Data Channels*	1
Measurement Averaging	No
Cable Length Available	2 m (6.6 ft)
Length of Smart Sensor Network Cable*	0.5 m (1.6 ft)

The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).