



- T-SDX-93720-105-010 • T-SDX-93720-105-020 • T-SDX-93720-105-030 •
- T-SDX-93720-105-050 • T-SDX-93720-105-100 • T-SDX-93720-110-010 •
- T-SDX-93720-110-020 • T-SDX-93720-110-030 • T-SDX-93720-110-050 •
- T-SDX-93720-110-100 • T-SDX-93720-135-020 • T-SDX-93720-135-030 •
- T-SDX-93720-135-050 • T-SDX-93720-135-100 • T-SDX-93720-150-050 •
- T-SDX-93720-150-100

Stevens SDX Pressure Sensor

Discontinued

The Stevens SDX (Submersible Depth Transmitter) is a high-accuracy water level/depth sensor that works with Onset's HOBOTM RX3000 cellular weather station to bring your water level data to the web



Compatible with
LI-COR Cloud[®] IoT Platform

Supported Measurements

Remote Water Level Monitoring, Water Level, Water Pressure

Features

- Rugged housing and fully-potted electronics ensure reliability, even in hostile fluid environments
- Provides remote access to water level data when paired with HOBOTM RX3000 weather stations via Onset's web platform, HOBOLink.com
- Custom-length cables enable use in a wide range of wells
- Typically provides +/- 0.1% accuracy (full scale)
- Ideal for groundwater and aquifer monitoring, stream and river gaging, and storm surge monitoring and more

Note: A calibration certificate is not included with the purchase of this sensor. If you require a calibration certificate, please call sales at 1-

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Stevens SDX Pressure Sensor (T-SDX-93720-xxx-xxx) Specifications

Power requirements	9 - 30 VDC
Output	4-20 mA current signal, linearly corresponding to range
Operating temperature	-40° F to 185° F (-40° C to 85° C)
Compensated temperature	32° F to 122° F (0° C to 50° C)
Linearity	0-5 ft range: 0.2% max. 0-10 ft range: 0.2% max. 0-35 ft range: 0.3% max. 0-50 ft range: 0.3% max. (0.1% typical for all ranges)
Repeatability & hysteresis	Typical: ± 0.2% span
Reverse polarity protection	Built into sensor
Overpressure	0-5 ft: 20 psi max. 0-10 ft: 20 psi max. 0-35 ft: 45 psi max. 0-50 ft: 45 psi max.
Shock	Qualification tested to 150 g
Wiring	Red: power Green: 4-20 mA return Silver: drain wire
Pipe threading	1/2-14 straight pipe thread (back of sensor housing near cable) 3/8-18 straight pipe thread (under removable copper nose-cone)
Physical size	4.00" L x 0.84" dia. (101.6 mm L x 21.33 mm dia.)
Weight	Probe: 2.37 oz (61.19 g) Cable: 0.43 oz (12.19 g) per foot (.4 g per cm) (weights are approximate)

Part Numbers:

T-SDX-93720-105-010
 T-SDX-93720-105-020
 T-SDX-93720-105-030
 T-SDX-93720-105-050
 T-SDX-93720-105-100
 T-SDX-93720-110-010
 T-SDX-93720-110-020
 T-SDX-93720-110-030
 T-SDX-93720-110-050
 T-SDX-93720-110-100
 T-SDX-93720-135-020
 T-SDX-93720-135-030
 T-SDX-93720-135-050
 T-SDX-93720-135-100
 T-SDX-93720-150-050
 T-SDX-93720-150-100