

CX603



InTemp 365-Day Dry Ice Temperature Logistics Monitoring

Multi-use Bluetooth temperature data logger for dry ice Cold Chain shipments

GXP compliant temperature IoT data logger ideal for Life Science and Pharmaceutical Cold Chain logistics for dry ice to ambient conditions. Ideal applications: General pharmaceutical and vaccine shipment and warehouse monitoring. Meets global Cold Chain, FDA, and EU regulatory requirements.

Important Information

Remote monitoring, process automation, and alarm notifications require the CX5001 Gateway. Gateway and mobile devices must be within 100ft (30.5m) Bluetooth range for data transmission.



Compatible with
InTemp Mobile App
InTempConnect[®]
InTempVerify
InTemp Wi-Fi/Ethernet IoT Gateway

Supported Measurements

Temperature

Features

- IATA Battery compliant
- 3-Point NIST Certificate of Calibration, valid for one year from date of purchase
- Anti-cut sheath
- Integrates with mobile and cloud platforms for a 21 CFR Part 11 compliant solution
- Compact and lightweight – ideal for shipping pharmaceuticals
- No need to open containers to access data
- Ensures secure data via encrypted technology

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- 1-508-743-3309 (US & International)
- +45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online www.onsetcomp.com/intemp/contact/support

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

InTemp 365-Day Dry Ice Temperature Logistics Monitoring (CX603) Specifications

Temperature Probe

Sensor Range	-95° to 50°C (-139° to 122°F)
Accuracy	±1.5°C from -95° to -40°C (±2.7°F from -139° to -40°F) ±1.0°C from -40° to -10°C (±1.8°F from -40° to 14°F) ±0.5°C from -10° to 50°C (±0.9°F from -14° to 122°F)
Resolution	0.013°C at 25°C (0.023°F at 77°F)
NIST Calibration	Three-point NIST calibration, probe only @ -70C, -10C, and 5C
Cable Length	1.5 m (4.92 ft)
Probe Dimensions	Food-grade stainless steel probe with blunt tip, 31.75 mm (1.25 inches) long, 4.78 mm (0.188 inches) diameter

Logger

Logger Operating Range	-30° to 50°C (-22° to 122°F)
Radio Power	1 mW (0 dBm)
Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
Wireless Data Standard	Bluetooth Low Energy (Bluetooth Smart)
Type	Multiple use
Duration	365 days
Shelf Life	Up to 1 year
Logging Rate	1 second to 18 hours
Battery	CR2450 3V lithium, not replaceable. Battery life is 1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive downloads, and paging may impact battery life
Memory	16,000 measurements
Full Memory Download Time	Approximately 30 seconds; may take longer the farther the device is from the logger
Dimensions	6.9 x 4.5 x 1.1 cm (2.71 x 1.76 x 0.42 inches)
Weight	25.5 g (0.90 oz)
Environmental Rating	IP65

Notices

Passed RTCA DO160G, part 21H

