



## HOBO® U20L Series Water Level Loggers

**A new standard for price/performance**

HOBO U20L Series Water Level loggers set a new standard for price/performance for accurate water level and temperature monitoring. The loggers combine 0.1% measurement accuracy, a polypropylene housing for use in both fresh and salt water, and a non-vented design for convenient and hassle-free deployment.

**Supported Measurements:** Water Level, Barometric Pressure, Pressure (Absolute), Temperature

### Key Advantages:

- Self-contained, non-vented design enables easy deployment
- Ideal for use in both fresh and saltwater environments
- Durable ceramic pressure sensor
- Ideal for use in wells, streams, lakes, wetlands and tidal areas

### Minimum System Requirements:



Software



Base Station<sup>1</sup>



Coupler<sup>2</sup>



<sup>1</sup>HOBO Base Station or HOBO Waterproof Shuttle required. See page 39 for more details.  
<sup>2</sup>Coupler included with HOBO Base Station or HOBO Waterproof Shuttle.

► For complete information and accessories, please visit: [www.onsetcomp.com](http://www.onsetcomp.com)

Part number	U20L-04	U20L-01	U20L-02
<b>HOBO Water Level Specifications</b>			
<b>Range</b>	0-4 m (0-13 ft) 0 to 145 kPa (0 to 21 psia)	0-9 m (0-30 ft) 0 to 207 kPa (0 to 30 psia)	0-30.6 m (0-100 ft) 0 to 400 kPa (0 to 58 psia)
<b>Factory Calibrated Range (0° to 40°C; 32° to 104°F)</b>	69 to 145 kPa (10 to 21 psia)	69 to 207 kPa (10-30 psia)	69 to 400 kPa (10 to 58 psia)
<b>Water Level Accuracy (Typical Error)</b>	± 0.4 cm (0.013 ft) (± 0.1% FS)	± 1.0 cm (0.03 ft) (± 0.1% FS)	± 3.0 cm (0.1 ft) (± 0.1% FS)
<b>Resolution</b>	0.14 cm (0.005 ft) water	0.21 cm (0.007 ft) water	0.41 cm (0.013 ft) water
<b>Burst Pressure</b>	310 kPa (45 psia) 18 m (60 ft) depth	310 kPa (45 psia) 18 m (60 ft) depth	500 kPa (72.5 psia) 40.8 m (134 ft) depth
<b>Temperature Specifications (all models)</b>			
<b>Range</b>	-20° to 50°C (-4° to 122°F)		
<b>Accuracy</b>	± 0.37° @ 20°C (± 0.67° @ 68°F)    ± 0.44° from 0° to 50°C (± 0.79° from 32° to 122°F)		
<b>Resolution (10 bit)</b>	0.1° @ 20°C (0.18° @ 68°F)		
<b>Response time</b>	10 minutes (to 90% in water)		
<b>Dimensions</b>	3.18 cm diameter x 15.24 cm (1.25 x 6.0 in) hole in mounting bail 6.3 mm (0.25 in)		
<b>CE compliant</b>	Yes		

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- Contact Product Support [onsetcomp.com/support/contact](http://onsetcomp.com/support/contact)
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532